EP 109

REV 03

IDENTIFICATION		
Chemical Name	SILICONE RUBBER USIHD70 - 20KG	
Formula	Not available	
CAS No.	Not available	

PHYSICAL-CHEMICAL CHARACTERISTICS					
Aspect	Translucent				
Characteristic	Unit	Minimum	Maximum	Method	
Tensile strength	MPa	6	-		
Elongation	%	% 200		Manufacturer's	
Break strength	KN/m	15	-	specification	
Hardness	Shore A	67	73		

MAJOR APPLICATIONS

Chemical, electrical and electronic industries, iron-steel works and automotive. Manufacture of resistance terminals, home appliances, wires and cables, hoses, profiles, automotive parts, electronic products, highvoltage insulators, furnace and oven sealing, sealing joints of automotive engines, etc.

OTHER INFORMATION				
UN No.	Product does not fit in the Resolution in force for transportation of hazardous products.			
Risk No.	Product does not fit in the Resolution in force for transportation of hazardous products.			
Package	Box with 20Kg of the product			
Cautions	Non-hazardous product. Handle the product in a place with natural or mechanical ventilation. As a good practice, we recommend the use of mask for organic vapors. The product does not emit vapors at ambient temperature. In case of sickness or persistent irritation, look for medical care. Use the PPEs below to handle: Rubber gloves (PVC, nitrile or latex), boots and protection goggles.			
Storage	Store in covered and vented place at ambient temperature.			
Validity	6 months, depending on the ideal storage conditions.			
Legal Requirements	Product does not fit in the Resolution in force for transportation of hazardous products.			

Technical sheet	Code	Description
	219.12.7	SILICONE RUBBER USIHD70 – 20 KG

CHANGE HISTORY				
Date	Revision Remarks			
-	01	Update of information at field for the major applications		
-	02	The specification number changed from EP 113 to EP 109 for system adjustment.		
-	03	Revision of the form with update of the company logo.		

F.CQ-0001 rev03 Page 1 of 1